Order form - AutoTrend Insulated Sectional Garage Door GSW 40-L



| Date: | Customer Order Number: | | | | | Number of Sheets: | |
|---|--|--|---|------------------------------------|-------------------------------|---|-------------------------------|
| Customer Name: | Contact Number: | | | | | | |
| Deliver To: | | | | Delivery Required Week Commencing: | | | |
| Door Ordering Width: 115mm Standard Headroom Notes: | or Ordering Height: Quantity (no extra cost) | | | Quantity | | | |
| Panel Profile: Georgian Standard Rib Centre Ribbed Solid Panel Surface (Inside Stucco): Woodgrain Smooth Panel Colour RAL 9002 Inside: White (RAL 9016) Black (RAL 9005) Anthracite Grey(RAL 7016) Trend: Frame Colour: White (RAL 9016) Black (RAL 9005) Anthracite Grey(RAL 7016) Trend: Frame Type: Back Fix Between Fix With Holes Between Fix (No Holes) Max size 5500 w x 2250mm h 85mm Frame Leg 3D Profile Ki Trend: Between Reveal Bracket Kit 120mm Leg/120mm Head 3D Profile Ki Trend: 85mm 3D Frame Leg/Additional Door Header Trend: 70mm Angle 3D Renovating Profil Trend: | | | | | | | |
| Type Rectangle 1 61 Type Cross Mullion 1 61 Type Rhombus 1 61 Type Rectangular 2 68 Type Rectangular 3 98 Type Square 1 Polymer 27 | Tro 10 x 270 | Type Aluminiu Type Aluminiu Type Aluminiu | m Sigma 610 m Zeta Ø 2 m Gamma 534 m Kappa 186 m Athena 406 | 0 x 280 | of the y require spread | describe the position windows and/or decals ed. Eg, top panel evenly do retrically aligned on to rvertically aligned on | 6 panel 5 panel 4 panel |
| Glazing Polymer: Clear Frame Colour: Trend/+: RAL: Width: Height: Opening: Style: Surface Colour: Trend/+: | Frosted Satin Qty: | Type Acc | ess 1 431 x 40 ess 2 430 x 40 ess 3 215 x 40 ess 4 400 x 86 ess 5 180 x 18 ess 6 70 x 70 ess 7 150 x 15 Letter Box Fitting (customer s | 30 | Type A Type A Quantity: Type | Access 8 194 x 194 Access 9 436 x 40 Access 10 431 x 13 Writing 1 100 2 Writing 2 200 2 Floor seal Qty: | House No. Required: |
| Operator: CarTeck MOTOR: AutoTrend doors come with a CarTeck MOTOR as standard: Doors UP TO 4877mm wide x 2250mm high are supplied with the CarTeck MOTOR L60 and doors OVER 4877mm wide x 2250mm high are supplied with the CarTeck MOTOR L75. Doors over 2500mm high are supplied with a rail extension which is included in the doors overall price. Accessories: Transmitter 4 channel MyQ Gateway with photocells MyQ LED Radio Light Photocells Wireless digital key pad Wireless 2-channel wall control Manual Locking: Factory On-Site External Release 101 Towing Arm Track cut-down Requirement: | | | | | | | |
| Notes | | | | OTAL £ | | SAVE FORM R | RESET FORM |